

2017 OUTLANDER™ XT 570

HIGHLIGHTS

- Rotax® V-Twin engine
- Continuously Variable Transmission (CVT) with engine braking
- Tri-Mode Dynamic Power Steering (DPS™)
- 3,000-lb (1,361 kg) WARN[†] winch with roller fairlead
- Heavy-duty front and rear bumpers
- 12-in. cast-aluminum wheels
- 25-in. Maxxis[†] M923J radial tires
- Double A-arm front suspension
- Torsional Trailing arm Independent (TTI) rear suspension
- Wind deflectors
- 500-W magneto
- Steel racks with LinQ quick-attach accessory system and a combined 360 pounds (163.3 kg) capacity
- 2.9-gal (10.9 L) water-resistant rear compartment



Yellow / 570
Pure Magnesium / 570

ENGINE

570

Type	48 hp, Rotax 570 cc V-twin, liquid cooled
Fuel Delivery System	Electronic Fuel Injection (EFI)
Transmission	CVT, P / R / N / H / L, standard engine braking
Drive Train	Selectable 2WD / 4WD with Visco-Lok QE auto-locking front differential
Power Steering	Tri-Mode Dynamic Power Steering (DPS)

SUSPENSIONS

Front Suspension	Double A-arm 9 in. (22.9 cm) travel
Front Shocks	Oil
Rear Suspension	Torsional Trailing arm Independent (TTI) 8.8 in. (22 cm) travel
Rear Shocks	Oil

BRAKES

Front	Dual 214 mm ventilated disc brakes with hydraulic twin-piston calipers
Rear	Single 214 mm ventilated disc brake with hydraulic twin-piston caliper

TIRES / WHEELS

Front Tires	Maxxis M923J 25 x 8 x 12 in. (63.5 x 20.3 x 30.5 cm)
Rear Tires	Maxxis M923J 25 x 10 x 12 in. (63.5 x 25.4 x 30.5 cm)
Wheels	12-in. cast-aluminum

DIMENSIONS / CAPACITIES

L x W x H	83 x 46 x 49 in. (211 x 116.8 x 124 cm)
Wheelbase	51 in. (129.5 cm)
Ground Clearance	10.5 in. (26.7 cm)
Seat Height	33.8 in. (85.8 cm)
Engine / Dry Weight*	704 lb (319 kg)
Rack Capacity	Front: 120 lb (54.4 kg) Rear: 240 lb (109 kg)
Storage Capacity	Rear: 2.9 gal (10.9 L)
Towing Capacity	1,300 lb (590 kg)
Fuel Capacity	5.4 gal (20.5 L)

FEATURES

Gauge	Multifunction Digital: Speedometer, tachometer, odometer, trip & hour meters, fuel, gear position, 4 x 4 indicator, diagnostics, clock	Instrumentation	Lighter type DC outlet in console, standard connector in the back (15-A)
Winch	3,000-lb (1,361 kg) WARN winch with roller fairlead	Lighting	70 W from dual 35-W front light / brake light
Protection	Heavy-duty front & rear bumpers Handlebar wind deflectors	Seat	Standard
		Anti-theft System	N/A

WARRANTY

Factory	6-months limited warranty
Extended	Up to 36 months B.E.S.T. coverage



©2016 Bombardier Recreational Products Inc. (BRP). All rights reserved.™, ® and the BRP logo are registered trademarks of BRP or its affiliates. Products are distributed in the U.S.A. by BRP US Inc. *Base model dry weight shown. †Visco-Lok is a trademark of GKN Viscodrive GmbH. All other trademarks are the property of their respective owners. Because of our ongoing commitment to product quality and innovation, BRP reserves the right at anytime to discontinue or change specifications, price, design, features, models or equipment without incurring any obligation. Ride responsibly. BRP highly recommends that all ATV drivers take a training course. For safety and training information, see your dealer or, in U.S.A. call the ATV Safety Institute at 1 (800) 887-2887. In Canada, call the Canadian Safety Council at 1 (613) 739-1535 ext 227. ATVs can be hazardous to operate. For your safety: the operator and passenger should wear a helmet, eye protection and other protective clothing. Always remember that riding and alcohol / drugs don't mix. Never ride on paved surfaces or public roads. Never engage in stunt driving. Avoid excessive speeds and be particularly careful on difficult terrain. ATVs with engine sizes of greater than 90cc are recommended for use only by those age 16 and older. Never carry passengers on any ATV not specifically designated for such use.

can-am

Can-AmOffroad.com

