

# 2017 RENEGADE<sup>®</sup> X<sup>®</sup> mr 570

## HIGHLIGHTS

- Rotax<sup>®</sup> snorkeled V-Twin engine with relocated CVT intake and outlet
- 28-in. Maxxis Mudzilla<sup>†</sup> tires
- 12-in. cast-aluminum beadlock wheels
- Tri-Mode Dynamic Power Steering (DPS<sup>™</sup>)
- Front and rear FOX<sup>†</sup> HPG shocks
- Torsional Trailing arm Independent (TTI) rear suspension
- Heavy-duty front and rear bumpers
- Aluminum taper-profile handlebar with grab handle, wind deflectors, and square pad
- Continuously Variable Transmission (CVT)
- Mudguards
- Multifunction digital gauge
- X-package coloration, graphics and seat cover



White, Black & Can-Am Red / 570

## ENGINE

### 570

Type	48 hp, Rotax 570 cc V-twin, snorkeled, liquid cooled
Fuel Delivery System	Electronic Fuel Injection (EFI)
Transmission	CVT, P / R / N / H / L, standard engine braking
Drive Train	Selectable 2WD / 4WD with Visco-Lok QE <sup>‡</sup> auto-locking front differential
Power Steering	Tri-Mode Dynamic Power Steering (DPS)

## SUSPENSIONS

Front Suspension	Double A-arm
Front Shocks	FOX HPG
Rear Suspension	Torsional Trailing arm Independent (TTI)
Rear Shocks	FOX HPG

## BRAKES

Front	Dual 214 mm ventilated disc brakes with hydraulic twin-piston calipers
Rear	Dual 214 mm ventilated disc brakes with hydraulic twin-piston calipers

## TIRES / WHEELS

Front Tires	Maxxis Mudzilla 28 x 8 x 12 in. (71.1 x 20.3 x 30.5 cm)
Rear Tires	Maxxis Mudzilla 28 x 10 x 12 in. (71.1 x 25.4 x 30.5 cm)
Wheels	12-in. cast-aluminum beadlock

## DIMENSIONS / CAPACITIES

L x W x H	83 x 50 x 56 in. (224 x 127 x 131 cm)
Wheelbase	51 in. (129.5 cm)
Ground Clearance	12 in. (30.5 cm)
Seat Height	35.25 in. (89.5 cm)
Engine / Dry Weight*	852 lb (386 kg)
Rack Capacity	Rear: 35 lb (16 kg)
Storage Capacity	N/A
Towing Capacity	1,300 lb (590 kg)
Fuel Capacity	5.4 gal (20.5 L)

## FEATURES

Gauge	Multifunction Digital: Speedometer, tachometer (bar graph RPM, bottom bar numerical RPM), odometer, trip & hour meters, diagnostic center, gear position, engine hour meter, 4 x 4 indicator, temperature and engine lights, fuel gauge, clock	Instrumentation	Lighter type DC outlet in console, standard connector in the back (15-A)
Winch	Prewired for available winch	Lighting	240 W from 4 fender mounted projector beam headlamps (60 W) with tail light / brake light
Protection	Front & rear bumpers, aluminum taper-profile handlebar with grab handle, wind deflectors and square pads, mudguards	Seat	Standard
		Anti-theft System	RF Digitally Encoded Security System (D.E.S.S.™)

## WARRANTY

Factory	6-months limited warranty
Extended	Up to 36 months B.E.S.T. coverage



©2016 Bombardier Recreational Products Inc. (BRP). All rights reserved. <sup>™</sup>, <sup>®</sup> and the BRP logo are registered trademarks of BRP or its affiliates. Products are distributed in the U.S.A. by BRP US Inc. <sup>†</sup>Base model dry weight shown. <sup>‡</sup>Visco-Lok is a trademark of GKN Viscodrive GmbH. All other trademarks are the property of their respective owners. Because of our ongoing commitment to product quality and innovation, BRP reserves the right at anytime to discontinue or change specifications, price, design, features, models or equipment without incurring any obligation. Ride responsibly. BRP highly recommends that all ATV drivers take a training course. For safety and training information, see your dealer or, in U.S.A. call the ATV Safety Institute at 1 (800) 887-2887. In Canada, call the Canadian Safety Council at 1 (613) 739-1535 ext 227. ATVs can be hazardous to operate. For your safety: the operator and passenger should wear a helmet, eye protection and other protective clothing. Always remember that riding and alcohol / drugs don't mix. Never ride on paved surfaces or public roads. Never engage in stunt driving. Avoid excessive speeds and be particularly careful on difficult terrain. ATVs with engine sizes of greater than 90cc are recommended for use only by those age 16 and older. Never carry passengers on any ATV not specifically designed for such use.

**can-am**

Can-AmOffroad.com

