

2018

RENEGADE[®] ADRENALINE

PACKAGE HIGHLIGHTS

- RAS™ 2 front suspension
- REV-XS™ platform
- rMotion™ rear suspension
- 15 x 137 x 1.25 in. RipSaw® track
- HPG™ Plus aluminum front shocks
- Pilot™ 5.7 skis
- Brembo brake with braided stainless-steel brake line
- RER™ electronic reverse
- Analog gauge with display
- Electric fuel gauge
- 15 in. / 38 cm windshield with integrated hand wind deflectors
- Painted tunnel
- RF D.E.S.S.™ key
- REV-XP™ X seat with 5 L / 1.3 US gal of storage

EXTRA HIGHLIGHTS

- 900 ACE & 1200 4-TEC®
- Mechanical reverse
- Reversible throttle lever (thumb or finger activated)
- iTC™ Engine mapping modes (Standard, Sport or ECO®)
- Engine oil cooler
- Learning Key included
- Extended heat exchanger for better cooling capacity



RENEGADE[®] ADRENALINE 600 H.O. E-TEC[®] shown

ROTAX[®] ENGINE

Engine details	600 H.O. E-TEC [®]	900 ACE	1200 4-TEC [®]
Cylinders	2	3	3
Displacement	594.4 cc / 36.3 in. ³	899 cc / 54.9 in. ³	1,170.7 cc / 71.4 in. ³
Bore	72 mm / 2.8 in.	74 mm / 2.9 in.	91 mm / 3.6 in.
Stroke	73 mm / 2.9 in.	69.7 mm / 2.7 in.	60 mm / 2.4 in.
Maximum engine speed	8,100 RPM	7,250 RPM	7,800 RPM
Carburation	Electronic Direct Injection	EFI	EFI
Recommended fuel type	Premium unleaded	Regular unleaded	Regular unleaded
Minimum octane	91	87	87
Fuel tank	40 L / 10.6 US gal	40 L / 10.6 US gal	40 L / 10.6 US gal
Oil tank capacity	3.7 L / 3.9 qt	3.3 L / 3.5 qt	3.5 L / 3.7 qt

POWERTRAIN

	600 H.O. E-TEC [®]	900 ACE	1200 4-TEC [®]
Drive clutch type	TRA™ III	eDrive™ 2	eDrive™ 2
Driven clutch type	QRS	QRS (short shaft)	QRS
Engagement	3,400 RPM	2,200 RPM	2,200 RPM
Small sprocket number of teeth	23	24	24
Large sprocket number of teeth	45	49	45
Drive sprocket number of teeth	8	8	8
Drive sprocket diameter	183 mm / 7.2 in.	183 mm / 7.2 in.	183 mm / 7.2 in.
Brake system	Brembo brake with braided stainless-steel brake line	Brembo brake with braided stainless-steel brake line	Brembo brake with braided stainless-steel brake line

DRY WEIGHT

600 H.O. E-TEC [®]	216 kg / 477 lb
900 ACE	228 kg / 503 lb
1200 4-TEC [®]	239 kg / 528 lb

FEATURES

Frame	REV-XS™	Starter	Electric	Mirrors	Optional
Skis	Pilot™ 5.7	Reverse	RER™ (600 H.O. E-TEC), Mechanical (900 ACE, 1200 4-TEC®)	Windshield	375 mm / 15 in.
Seating	REV-XP™ X with storage	Heated throttle lever	Standard	Runner	Square 5/16
Handlebar	Aluminum with J-hooks	Heated grips	Standard	Carbide configuration	102 mm / 4 in. at 90°
Riser block height	115 mm / 4.5 in.	Gauge	Analog with display	Hitch	Optional

COLOR

White / Orange Crush 
Black 

DIMENSIONS

Vehicle overall length	3,110 mm / 122.4 in.
Vehicle overall width	1,217 mm / 47.9 in.
Vehicle overall height	1,210 mm / 47.6 in.
Ski stance	1,077 mm / 42.4 in.
Ski overall length	1,066 mm / 42 in.
Track nominal width	381 mm / 15 in.
Track nominal length	3,487 mm / 137 in.
Track profile height	31.8 mm / 1.25 in. RipSaw®

SUSPENSION

Front suspension	RAS™ 2
Front shock	HPG™ Plus
Front suspension max. travel	220 mm / 8.7 in.
Rear suspension	rMotion™
Center shock	HPG™
Rear shock	HPG™
Rear suspension max. travel	270 mm / 10.6 in.



RENEGADE® ADRENALINE 1200 4-TEC® shown



RENEGADE® ADRENALINE 900 ACE shown

FEATURE HIGHLIGHTS



RAS™ 2 Front suspension

A taller ski spindle, refined geometry and lighter components sharpen the sled's already precise handling, especially in extreme conditions.



RF D.E.S.S.™ Key

D.E.S.S.™ security system on most models uses Radio Frequency technology for peace of mind. The ball-and-socket design ensures a solid connection in all conditions.



rMotion™ suspension

Sets new standards in comfort, capability and adjustability.



LinQ™ cargo system (option)

Our cargo attachment system is the hassle-free way to connect cargo bags or a fuel caddy to your sled in seconds.



Analog gauge with display

GAUGE FEATURES

Speedometer	Standard
Tachometer	Standard
Fuel	Standard
Engine temperature	Optional