

2018

RENEGADE[®] ENDURO[™]

PACKAGE HIGHLIGHTS

- Heated REV-XP™ X seat with 5 L / 1.3 US gal of storage
- RAS™ 2 front suspension
- REV-XS™ platform
- rMotion™ with Air Ride rear suspension
- 15 x 137 x 1.25 in. Ice Ripper XT track
- HPG™ Plus aluminum front shocks
- Adjustable Pilot™ TS Skis
- Brembo brake with braided stainless-steel brakeline
- RER™ electronic reverse (E-TEC® engines)
- Multi-function digital gauge with display
- 12V power outlet and heated visor outlet for driver
- RF D.E.S.S.™ key

EXTRA HIGHLIGHTS

- 900 ACE & 1200 4-TEC®
- Reversible throttle lever (thumb or finger activated)
- iTC™ Engine mapping modes (Standard, Sport or ECO®)
- Learning Key included
- Engine oil cooler
- Mechanical reverse
- Extended heat exchanger for better cooling capacity

800R E-TEC[®] shown

ROTAX [®] ENGINE	600 H.O. E-TEC [®]	800R E-TEC [®]	900 ACE	1200 4-TEC [®]
Engine details	Liquid-cooled, 3-D.R.A.V.E.™	Liquid-cooled, 3-D.R.A.V.E.™	Liquid-cooled, four-stroke D.O.H.C., dry sump	Liquid-cooled, four-stroke D.O.H.C., dry sump
Cylinders	2	2	3	3
Displacement	594.4 cc / 36.3 in. ³	799.5 cc / 48.8 in. ³	899 cc / 54.9 in. ³	1,170.7 cc / 71.4 in. ³
Bore	72 mm / 2.8 in.	82 mm / 3.2 in.	74 mm / 2.9 in.	91 mm / 3.6 in.
Stroke	73 mm / 2.9 in.	75.7 mm / 3 in.	69.7 mm / 2.7 in.	60 mm / 2.4 in.
Maximum engine speed	8,100 RPM	7,900 RPM	7,250 RPM	7,800 RPM
Carburation	Electronic Direct Injection	Electronic Direct Injection	EFI	EFI
Recommended fuel type	Premium unleaded	Premium unleaded	Regular unleaded	Regular unleaded
Minimum octane	91	91	87	87
Fuel tank	40 L / 10.6 US gal	40 L / 10.6 US gal	40 L / 10.6 US gal	40 L / 10.6 US gal
Oil tank capacity	3.7 L / 3.9 qt	3.7 L / 3.9 qt	3.3 L / 3.5 qt	3.5 L / 3.7 qt

POWERTRAIN

Drive clutch type	TRA™ III	TRA™ VII	eDrive™ 2	eDrive™ 2
Driven clutch type	QRS	QRS	QRS (short shaft)	QRS
Engagement	3,400 RPM	3,800 RPM	2,200 RPM	2,200 RPM
Small sprocket number of teeth	23	25	24	24
Large sprocket number of teeth	45	45	49	45
Drive sprocket number of teeth	8	8	8	8
Drive sprocket diameter	183 mm / 7.2 in.	183 mm / 7.2 in.	183 mm / 7.2 in.	183 mm / 7.2 in.
Brake system	Brembo brake with braided stainless-steel brake line	Brembo brake with braided stainless-steel brake line	Brembo brake with braided stainless-steel brake line	Brembo brake with braided stainless-steel brake line

DRY WEIGHT

232 kg / 513 lb	237 kg / 523 lb	243 kg / 537 lb	251 kg / 555 lb
-----------------	-----------------	-----------------	-----------------

FEATURES

Frame	REV-XS™	Starter	Electric	Mirrors	Optional
Skis	Pilot™ TS	Reverse	RER™ (600 H.O. E-TEC, 800R E-TEC), Electronic (900 ACE, 1200 4-TEC®)	Windshield	375 mm / 15 in.
Seating	REV-XP™ X heated with storage	Heated throttle lever	Standard	Runner	Adjustable blade 1/4
Handlebar	Aluminum with J-hooks	Heated grips	Standard	Carbide configuration	102 mm / 4 in. at 90°
Riser block height	115 mm / 4.5 in.	Gauge	Multifunction	Hitch	Optional

COLOR

Lava Red / Tactical Grey
Black

DIMENSIONS

Vehicle overall length	3,110 mm / 122.4 in.
Vehicle overall width	1,217 mm / 47.9 in.
Vehicle overall height	1,210 mm / 47.6 in.
Ski stance	1,077 mm / 42.4 in.
Ski overall length	1,066 mm / 42 in.
Track nominal width	381 mm / 15 in.
Track nominal length	3,487 mm / 137 in.
Track profile height	31.8 mm / 1.25 in. Ice Ripper XT

SUSPENSION

Front suspension	RAS™ 2
Front shock	HPG™ Plus
Front suspension max. travel	220 mm / 8.7 in.
Rear suspension	rMotion™
Center shock	HPG™
Rear shock	Air Ride
Rear suspension max. travel	270 mm / 10.6 in.



1200 4-TEC® shown



600 H.O. E-TEC® shown

FEATURE HIGHLIGHTS



RAS™ 2 Front suspension

A taller ski spindle, refined geometry and lighter components sharpen the sled's already precise handling, especially in extreme conditions.



Air Ride rear suspension

Tailors the ride for load or trail conditions via a rear air spring and an onboard compressor. Five preload settings are selectable on-the-fly via a handlebar rocker switch.



Adjustable Pilot™ TS Skis

Radical concept enables the rider to literally dial in the amount of ski bite for conditions and riding style in seconds. A knob adjacent to the ski leg raises or lowers the ski runner - fully extended for very aggressive bite. There are 20 settings over a 5 in. / 12.5 mm range.



LinQ™ cargo system (option)

Our cargo attachment system is the hassle-free way to connect cargo bags or a fuel caddy to your sled in seconds.



Analog gauge with display

GAUGE FEATURES

Speedometer	Standard
Tachometer	Standard
Fuel	Standard
Engine temperature	Standard