

2018

RENEGADE[®] X 850 E-TEC[®]

PACKAGE HIGHLIGHTS

- Rotax[®] 850 E-TEC[®] engine
- RAS[™] 3 front suspension
- REV[®] Gen4 platform
- pDrive[™] clutch
- Forward Adjustable Riser
- Ergo-step side panels
- Open toe-hold
- rMotion[™] rear suspension
- 15 x 137 in. track choice; 1.25 in. RipSaw⁺ or 1.25 in. Ice Ripper XT or **1.6 in. Ice Cobra**
- KYB[†] Pro 36 aluminum piggyback rear shock with Easy-Adjust compression adjusters (22 clics)
- HPG[™] Plus aluminum front shocks
- Brembo racing brake with braided stainless-steel brake line
- RER[™] electronic reverse
- Backlit multifunction steering controls
- Transparent handguards
- Performance trail seat
- Glove box with 4 L / 1 US gal of storage
- RF D.E.S.S.[™] key
- Optional Adjustment package including rMotion[™] Quick Adjust[™] system and Pilot[™] TS skis
- Rack steering system



RENEGADE[®] X 850 E-TEC[®] shown

ROTAX[®] ENGINE

	850E-TEC [®]
Engine details	Liquid-cooled, electronic R.A.V.E. [™]
Cylinders	2
Displacement	849 cc / 51.9 in. ³
Bore	82 mm / 3.2 in.
Stroke	80.4 mm / 3.2 in.
Maximum engine speed	7,900 RPM
Carburation	Electronic Direct Injection with additional booster injectors
Recommended fuel type	Premium unleaded
Minimum octane	91
Fuel tank	36 L / 9.5 US gal
Oil tank capacity	3.4 L / 3.6 qt

POWERTRAIN

Drive clutch type	pDrive [™]
Driven clutch type	QRS
Engagement	3,600 RPM
Small sprocket number of teeth	25 (Ripsaw, Ice Ripper XT) 23 (Ice Cobra 1.6)
Large sprocket number of teeth	45
Drive sprocket number of teeth	8
Drive sprocket diameter	183 mm / 7.2 in.
Brake system	Brembo racing brake with stainless-steel braided brake line

DRY WEIGHT

220 kg / 485 lb

FEATURES

Frame	REV [®] Gen4	Starter	Electric	Mirrors	Optional
Skis	Pilot [™] 5.7, Pilot [™] TS (optional)	Reverse	RER [™]	Windshield	360 mm / 14 in.
Seating	Trail performance	Heated throttle lever	Standard	Runner	Square 3/8
Handlebar	Aluminum with J-hooks	Heated grips	Standard	Carbide configuration	102 mm / 4 in. at 90°
Riser block height	Adjustable-120 mm / 4.7 in.	Gauge	Multifunction	Hitch	Optional

COLOR

Manta Green / Black

Black

DIMENSIONS

Vehicle overall length	3,124 mm / 123 in.
Vehicle overall width	1,217 mm / 47.9 in.
Vehicle overall height	1,222 mm / 48.1 in.
Ski stance	1,077 mm / 42.4 in.
Ski overall length	1,066 mm / 42 in.
Track nominal width	381 mm / 15 in.
Track nominal length	3,456 mm / 137 in.
Track profile height	31.8 mm / 1.25 in. RipSaw ⁺
Optional track	31.8 mm / 1.25 in. Ice Ripper XT 40.6 mm / 1.6 in. Ice Cobra

SUSPENSION

Front suspension	RAS [™] 3
Front shock	HPG [™] Plus
Front suspension max. travel	233 mm / 9.2 in.
Rear suspension	rMotion [™]
Center shock	HPG [™] Plus
Rear shock	KYB [†] Pro 36 EA
Rear suspension max. travel	270 mm / 10.6 in.



RENEGADE® X 850 E-TEC® shown



RENEGADE® X 850 E-TEC® shown

FEATURE HIGHLIGHTS



Rotax® 850 E-TEC® engine

Next generation of the most advanced direct-injection two-stroke engine technology. Designed for reliability and durability with proven 4-stroke and diesel technologies.



Ergo-Step side panels

Design offers natural progression to three natural positions for different cornering styles, including a new, extreme-forward position.



pDrive™ clutch

Fast and friction-free dual rollers transfer torque in place of traditional sliding buttons on this 100% new clutch. Ultra-responsive shifting, impressive RPM consistency and lightweight.



FAR steering

4 in. / 10 cm of no-tool fore-aft adjustment to customize the riding position instantly.



Multifunction gauge with LCD screen

GAUGE FEATURES

Speedometer	Standard
Tachometer	Standard
Fuel	Standard
Engine temperature	Standard