

BOONDOCKER 3700

2018



ROTAX® ENGINE

600 E-TEC

Engine details	Liquid-cooled, 3-D R.A.V.E.™
Cylinders	2
Displacement	594.4 cc
Bore	72 mm
Stroke	73 mm
Maximum engine speed	8100 RPM
Carburation	Electronic Direct Injection
Recommended fuel type	Premium unleaded
Minimum octane	95
Fuel tank	38 liters
Oil tank capacity (2-stroke)	3,5 liters

POWERTRAIN

Drive clutch type	TRA 3
Driven clutch type	QRS
Small sprocket number of teeth	19
Large sprocket number of teeth	49
Drive sprocket	8
Brake system	Hydraulic brake with braided steel brake line, plastic master cylinder

FEATURES

Frame	REX²
Skis	Blade DS
Seating	BD, 1-up
Handlebar	U-type steel, mountain strap
Riser block height	115 mm
Starter	Manual, Electric (BYR opt.)
Reverse	RER

COLOUR



Black

DIMENSIONS

Vehicle overall length	3170 mm
Vehicle overall width	1105 mm
Vehicle overall height	1280 mm
Ski stance	921 +/- 21 mm
Track nominal width	406 mm
Track nominal length	3705 mm
Track profile height	64 mm PowderMax FlexEdge

SUSPENSION

Front suspension	A-LFS+
Front shock	HPG 36
Rear suspension	PPS²-3700-DS
Center shock	HPG 36
Rear shock	HPG 36

Heated throttle lever	Standard
Heated grips	Standard
Gauge	Multifunction
Mirrors	Accessory
Windshield	XS / 140 mm
Hitch	Accessory

BOONDOCKER 3900

2018



ROTAX® ENGINE

600 E-TEC

Engine details	Liquid-cooled, 3-D R.A.V.E.™
Cylinders	2
Displacement	594.4 cc
Bore	72 mm
Stroke	73 mm
Maximum engine speed	8100 RPM
Carburation	Electronic Direct Injection
Recommended fuel type	Premium unleaded
Minimum octane	95
Fuel tank	38 liters
Oil tank capacity (2-stroke)	3,5 liters

POWERTRAIN

Drive clutch type	TRA 3
Driven clutch type	QRS
Small sprocket number of teeth	19
Large sprocket number of teeth	49
Drive sprocket	8
Brake system	Hydraulic brake with braided steel brake line, plastic master cylinder

FEATURES

Frame	REX²
Skis	Blade DS
Seating	BD, 1-up
Handlebar	U-type steel, mountain strap
Riser block height	115 mm
Starter	Manual, Electric (BYR opt.)
Reverse	RER

COLOUR

 Black

DIMENSIONS

Vehicle overall length	3300 mm
Vehicle overall width	1105 mm
Vehicle overall height	1280 mm
Ski stance	921 +/- 21 mm
Track nominal width	406 mm
Track nominal length	3923 mm
Track profile height	64 mm PowderMax FlexEdge

SUSPENSION

Front suspension	A-LFS+
Front shock	HPG 36
Rear suspension	PPS²-3900-DS
Center shock	HPG 36
Rear shock	HPG 36

BOONDOCKER 3900

2018



ROTAX® ENGINE

600 E-TEC

Engine details	Liquid-cooled, 3-D R.A.V.E.™
Cylinders	2
Displacement	594.4 cc
Bore	72 mm
Stroke	73 mm
Maximum engine speed	8100 RPM
Carburation	Electronic Direct Injection
Recommended fuel type	Premium unleaded
Minimum octane	95
Fuel tank	38 liters
Oil tank capacity (2-stroke)	3,5 liters

POWERTRAIN

Drive clutch type	TRA 3
Driven clutch type	QRS
Small sprocket number of teeth	19
Large sprocket number of teeth	49
Drive sprocket	8
Brake system	Hydraulic brake with braided steel brake line, plastic master cylinder

FEATURES

Frame	REX²
Skis	Blade DS
Seating	BD, 1-up
Handlebar	U-type steel, mountain strap
Riser block height	115 mm
Starter	Manual, Electric (BYR opt.)
Reverse	RER

COLOUR

 Black

DIMENSIONS

Vehicle overall length	3300 mm
Vehicle overall width	1105 mm
Vehicle overall height	1280 mm
Ski stance	921 +/- 21 mm
Track nominal width	406 mm
Track nominal length	3923 mm
Track profile height	64 mm PowderMax FlexEdge

SUSPENSION

Front suspension	A-LFS+
Front shock	HPG 36
Rear suspension	PPS²-3900-DS
Center shock	HPG 36
Rear shock	HPG 36