

2018 OUTLANDER™ PRO 450

HIGHLIGHTS

- Rotax® single cylinder engine
- Continuously Variable Transmission (CVT) with engine braking
- Tri-Mode Dynamic Power Steering (DPS)
- 12-in. cast-aluminum wheels
- 26-in. 6-ply Carlisle† ACT HD radial tires
- Reinforced seat skin
- Relocated air intakes
- Increased ground clearance
- NEW Digitally Encoded Security System (D.E.S.S.™)
- 590 kg towing capacity
- 500-W magneto
- Multifunction digital gauge
- Steel racks LinQ quick-attach accessory system and a combined 163.3 kg capacity
- 10.9 L water-resistant rear compartment



Green

ENGINES

450

| | |
|----------------------|---|
| Type | 38 hp, Rotax 427 cc single cylinder, liquid cooled |
| Fuel Delivery System | Electronic Fuel Injection (EFI) |
| Transmission | CVT, P / R / N / H / L, standard engine braking |
| Drive Train | Selectable 2WD / 4WD with Visco-Lok QE† auto-locking front differential |
| Power Steering | Tri-Mode Dynamic Power Steering (DPS) |

SUSPENSIONS

| | |
|------------------|--|
| Front Suspension | Double A-arm 22.9 cm travel |
| Front Shocks | Oil |
| Rear Suspension | Torsional Trailing arm Independent (TTI) 22.4 cm travel |
| Rear Shocks | Oil |

BRAKES

| | |
|-------|--|
| Front | Dual 214 mm ventilated disc brakes with hydraulic twin-piston calipers |
| Rear | Single 214 mm ventilated disc brake with hydraulic twin-piston caliper |

FEATURES

| | | | |
|------------|---|-------------------|---|
| Gauge | Multifunction Digital: Speedometer, tachometer, odometer, trip & hour meters, fuel, gear position, 4 x 4 indicator, diagnostics, clock | Instrumentation | Lighter type DC outlet in console, standard connector in the back (15-A) |
| Winch | Prewired for available winch | Lighting | 70-W from dual 35-W front light / brake light |
| Protection | N/A | Seat | Reinforced seat skin |
| | | Anti-theft System | Digitally Encoded Security System (D.E.S.S.™) |

WARRANTY

| | |
|---------|---------|
| Factory | 2 years |
|---------|---------|

TIRES / WHEELS

| | |
|-------------|--|
| Front Tires | Carlisle† ACT HD 26 x 8 x 12-in. (66 x 20.3 x 30.5 cm) |
| Rear Tires | Carlisle† ACT HD 26 x 10 x 12-in. (66 x 25.4 x 30.5 cm) |
| Wheels | 12-in. cast-aluminum |

DIMENSIONS / CAPACITIES

| | |
|------------------|--------------------------------|
| L x W x H | 211 x 116.8 x 124 cm |
| Wheelbase | 129.5 cm |
| Ground Clearance | 29.2 cm |
| Seat Height | 85.8 cm |
| Dry Weight* | 308 kg |
| Rack Capacity | Front: 54.4 kg Rear: 109 kg |
| Storage Capacity | Rear: 10.9 L |
| Towing Capacity | 590 kg |
| Fuel Capacity | 20.5 L |

©2017 Bombardier Recreational Products Inc. (BRP). All rights reserved.™ ® and the BRP logo are registered trademarks of BRP or its affiliates. Products are distributed in the U.S.A. by BRP US Inc. *Base model dry weight shown. †Visco-Lok is a trademark of GKN Viscodrive GmbH. All other trademarks are the property of their respective owners. Because of our ongoing commitment to product quality and innovation, BRP reserves the right at anytime to discontinue or change specifications, price, design, features, models or equipment without incurring any obligation. Ride responsibly. BRP highly recommends that all ATV drivers take a training course. For safety and training information, see your dealer or, in U.S.A. call the ATV Safety Institute at 1 (800) 887-2887. In Canada, call the Canadian Safety Council at 1 (613) 739-1535 ext 227. ATVs can be hazardous to operate. For your safety: the operator and passenger should wear a helmet, eye protection and other protective clothing. Always remember that riding and alcohol / drugs don't mix. Never ride on paved surfaces or public roads. Never engage in stunt driving. Avoid excessive speeds and be particularly careful on difficult terrain. ATVs with engine sizes of greater than 90cc are recommended for use only by those age 16 and older. Never carry passengers on any ATV not specifically designated for such use.

can-am



Can-AmOffroad.com